

Main Specification of CNC Pressbrake

Main Specifaion		Unit	PR								
Model			60x1500	60x2050	60x2550	100x3100 100x4100	150x3100 150x4100	225x3100 225x4100	320x3100 320x4100	400x3100 400x4100	500x6000 600x6000
Main Driving Type			Hydraulic								
Bending Force	KN		600	600	600	1000	1500	2250	3200	4000	5000 6000
Bending Length	mm		1500	2050	2550	3100 4100	3100 4100	3100 4100	3100 4100	3100 4100	6000
Column Distance	mm		1100	1600	2000	2600 3600	2600 3600	2600 3600	2600 3600	2600 3600	5100
Throat Depth	mm		300	300	300	400	400	400	400	400	400 500
Stroke of Ram	mm		165	165	165	215	215	215	265	265	315
Table Height	mm		830	830	830	830	830	830	830	830	900 1200
Table Width	mm		50	50	50	60 70	70 80	80 90	90 100	100 110	120
Closed Height	mm		420	420	420	420	420	480	530	530	580 600
Speed	Approaching	mm/s	150	150	150	160	120 130	110 120	80 90	100 110	90 80
	Working	mm/s	11	11	11	10	9	8	8	8	7 8
	Return	mm/s	120	120	120	130 120	110	90	85	85	70
Main Motor Power	KW		5.5	5.5	5.5	7.5	11	15	22	30	37
Oil Tank Capacity	L		200	250	300	350 500	400 600	400 550	450 600	440 600	880 800
Backgauge	Precision	mm	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.1	±0.2
	Stroke	mm	500	500	500	500	500	500	500	500	500
	Speed	mm/s	300	300	300	300	300	300	300	300	250
	Power	KW	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.85
Number of Oil Tank	pcs		1	2	3	3 4	3 4	3 4	3 4	3 4	6
Dimension L×W×H	mm		L:2350	L:2900	L:3400	L:3450 L:4450	L:3470	L:3940	L:3510	L:3460	L:6460
			W:1400	W:1400	W:1400	W:1600	W:1720	W:1960	W:2200	W:2150	W:2050
			H:2270	H:2270	H:2270	H:2510	H:2510	H:2760	H:3120	H:3300	H:3300

- ◆ **Note:** All the model can be designed into : processing size of 3100/4100/5000/6000/7000/8000 [mm]
Controlling axes can be designed into 3+1 axes/4+1 axes/5+1 axes/6+1 axes/7+1axes/8+1axes/10+1axes.
- ◆ **Note:** All the specifications are subjected to change without further notice.